

Steam boiler DM 2000



The DM 2000 is an industrial boiler that is flexible and is ready for immediate and independent use. The steam boiler is equipped with feed pumps, a storage tank for feed water and a Weishaupt fuel burner, which can be fired with oil. If necessary, an internal water treatment plant can also be used.

We can provide flexible steam hoses for quick installation.

Properties

- 100-2000 kg/h
- Standard 6 – 11 bar
- Compact design in 25ft. container
- Integrated feed pump
- Flexible hose connection, up to 16 bar
- Especially suitable for long-term rental

Specifications

Effect	kg/h	100 – 2000
Dimensions L x W x H	mm	8000 x 2550 x 2774
Transport weight	kg	11,000
Medium		Steam
Pressure SW	bar	Adjustable to 12 bar
Boiler adjustable range	bar	6– 11.1
Pressure reduction	bar	0.2 – 12
Maximum pressure	bar	12
Fuel		Oil
Safety		European Directive 97/23/EC (PED)
Frost protection		Yes
Remote control		Optional/alarm
Connection		CEE 16A 5 poles / 400V
Pipe		Steel
Flexible connection cable		Required
Water condensation connection		DN32/ PN16 Flange
Steam		DN 65 / PN 16 Flange
Blow-down		DN 40 / PN 16 Flange

Subject to technical changes