

Steam boiler DM 600



The DM 600 is an industrial boiler that is flexible and is ready for immediate and independent use. The steam boiler is equipped with feed pumps, a storage tank for feed water and a Weishaupt double fuel burner, which can be fired with either oil or natural gas. We can also include an external tank system and water treatment plant.

Properties

- 400-600 kg/h
- Compact design in 20ft. container
- Equipped with a dual-fuel burner
- Integrated feed pump
- Flexible hose connection, up to 16 bar
- Especially suitable for long-term rental

Specifications

Effect	kg/h	400 – 600
Dimensions L x W x H	mm	6050 x 2450 x 2880
Transport weight	kg	8000
Medium		Steam
Pressure SW	bar	Up to 16 bar with hoses, from 16 only with hard tube rod
Boiler adjustable range	bar	4.5 – 14
Pressure reduction	bar	0.2 – 17
Maximum pressure	bar	14
Fuel		Bio oil or LPG
Safety		TRD 604 / 24h / EN 12953
Frost protection		Yes
Remote control		Optional
Connection		CEE 32A 5 poles / 400V
Pipe		Steel
Flexible connection cable		Required
Water condensation connection	inches	1-2
Steam		DN 80 / PN 40 Flange
Blow-down		DN 25 / PN 40 Flange

Subject to technical changes