

Air heater AH 100



Thanks to installation on a robust sack trolley, the Air Heater AH 100 is quickly installed and is very flexible in use. The system is controlled by a thermostat mounted on the unit. In connection with System distribution. The CD 25 air heater can also be used as part of a larger heating group. Perfect for larger warehouses, or for drying larger buildings.

Properties

- 102 kW at 70/65°C
- Can be used for drying services / building drying or heating of events
- Ready to use
- Mounted on a sack trolley
- Easy to install yourself
- Shut-off valve
- Thermostat controlled

Specifications

Thermostat		Yes
Dimensions L x W x H	mm	1200 x 480 x 1150
Weight	kg	115
Efficiency 1st step	kW	86 kW (at 75/65°C air intake temp. +5°C, output temp. 44°C)
Efficiency 2nd step	kW	102 kW (at 75/65°C air intake temp. +5°C, output temp. +41°C)
Motor capacity level 1/2 (3 x 400V)	kW	0.36 / 0.53
Power consumption level 1/2 (3 x 400V)	A	0.62 / 1.0
Power connector	A/V	CEE 16A 5 poles / 400V
Steps		2
Range 1/2	M	22 / 32
Noise level 1/2	db(A)	57/61 db (A) at 5 metres, room size 1500 m ³
Flow 1/2	m ³ /h	6150 / 7960

Subject to technical changes